AMETHERM
Circuit Protection Thermistors

DATA SHEET

Part Number: SL12 40002

Ordering Different Lead Types:

Inside Kinked Leads	Use **-A** after Ametherm's part #
Outside Kinked Leads	Use **-B** after Ametherm's part #

For example: to order an inside kinked lead use part number SL12 40002-**A**



Electrical Specifications:

Resistance @ 25°C	40.0 Ω ± 25%
Max Steady State Current Up to 65°C	2.0 A
Max Recommended Energy Rating (Joules)	20.0 J
Actual Failure Point of Instantaneous Energy (Joules)	35.0 J
Resistance @ 100% of Max Current	0.450 Ω
Resistance @ 50% of Max Current	0.958 Ω
Body Temperature @ 100% Current Rating	148 °C
Dissipation Constant	12.7mW/°C
Thermal Time Constant	47 seconds
Material Type	"I"
Max Recommended Capacitance @120VAC/240VAC	1380µF/350µF

Mechanical Specifications:

D	12.0 ± 0.5 mm
T	5.1 ± 0.2 mm
Lead Diameter	0.8 ± 0.1 mm
S	7.8 ± 2.0 mm
L	38.0 ± 9.0 mm
Straight Leads Coating Run Down	5.0 ± 1.0 mm
B	6.35 ± 0.60 mm
C	3.42 ± 0.5 mm

CSA File Number: #CA118061 Revision Date: March 19, 2003

Ametherm, Inc. 3111 N. Deer Run Road #4 Carson City, NV 89701
Telephone: (800) 808-2434 (775) 884-2434 Fax: (775) 884-0670
www.ametherm.com